

SPECIFICATIONS



	HD 10-A	HD 12-A	HD 32-A
ACOUSTICAL			
Frequency response	50 - 20 kHz	45 - 20 kHz	45 - 20 kHz
Max SPL	129 dB	130 dB	131 dB
Horizontal Coverage	90°	90°	90°
Vertical Coverage	70°	60°	60°
Crossover point	1.700	1.600	800
TRANSDUCERS			
Low frequency	10", 2.5" v.c.	12", 2.5" v.c.	12", 2.5" v.c.
High frequency	1", 1.7" v.c.	1", 1.7" v.c.	2", 3.0" v.c.
AMPLIFIER			
Total power	600 Watt		700 Watt
Low section	450 Watt		500 Watt
High section	150 Watt		200 Watt
CONNECTIONS			
Signal input/output	Jack-XLR male / XLR female		Jack-XLR male / XLR female
Power input	VDE AC socket		Powercon AC socket
DSP and Protection Circuits	2 way equalisation, crossover filtering, Fast limiter, RMS limiter		2 way equalisation, crossover filtering, Fast limiter, RMS limiter
PHYSICAL SPECIFICATIONS			
Dimensions (w, h, d)	527, 303, 302 mm	647, 380, 380 mm	647, 380, 380 mm
Weight	13.9 Kg	16.7 Kg	18.6 Kg
Colour	Black	Black	Black